



Historical and chronological evolution of the concert hall acoustics parameters

R. Lacatis^a, A. Giménez^a, A. Barba Sevillano^a, S. Cerdá^a, J. Romero^a and R. Cibrián^b

^aGrup d'Acústica Arquitectònica, Ambiental i Industrial, E.T.S.I.I, Univ. Politècnica de Valencia, Camino de Vera, s/n, 46022 Valencia, Spain

^bFacultad de Medicina, Univ. de Valencia, Av. Blasco Ibáñez, 15, 46010 Valencia, Spain
rala1@doctor.upv.es

The present paper examines the historical evolution of the concert halls acoustic parameters, in the international field. From the beginnings of twentieth century, the acoustic parameters have had a continuous evolution, covering more and more aspects of the concert hall acoustics qualification.

Since the bibliography about these is fragmented, we performed in this article, a global and updated presentation on the chronology and the evolution of the studied parameters.

Considering the great variety of the same, we presents the appearance of each parameter, located in decades, who has proposed them and, where is possible, indicates articles or publications where they have been presented for the first time. Thus, the historical presentation of the majority of the acoustic parameters of concert halls, it optimizes and can be useful for future research as a central platform in a bibliographical study. The presentation of the same is also grouped according to quality criteria.

1 Introduction

The acoustics of halls, in our case the concert hall, has had a great development, since Clemens Wallace Sabine [1] If, initially the discovery of “the reverberation time” as persistence of the sound in an enclosure constituted the most important parameter in the evaluation of the hall (already from its definition is clearly a perceptive, subjective and multidisciplinary parameter), in the following decades, new descriptors are added to analyze and to design the existent halls as well as those in phase of construction. It is necessary to emphasize that the objective of the study, is not to present the parameters definitions that can be found in specialized bibliography, is the most possible complete review of the developed acoustic parameters throughout the time. At present the acoustic investigators have stated the existence of independent parameters and other interdependent ones, which had lead to a different approaches and a great diversity of scientific opinions on the matter. In this direction, Gimenez [2] studied the evolution of investigators groups of belonging to schools of: Dresden (Reichardt, Schmidt, Shultz, Cremer, Kürer), Goettingen (Gottlob, Siebrasse, Eysholdt and Schroeder), Berlin (Lehman and Wilkers), Japanese School (Hidaka, Maekawa, Morimoto, Okano) and acoustic as Ando, Barron, Beranek, Fricke, Gade, Haan, Marshall, Kahle, Farina. In the Spanish land, investigators from Universities of four Independent Communities (Catalonia, Navarre, Seville and Valencia), study the correlation between objectives parameters and the subjective answers of the listeners. [3].

2 Qualifying Parameters

The study it is initiated with Leo Leroy Beranek, due to the extensive study realized in the concerts hall acoustics research. . The parameters proposed by Beranek [4] are the following ones:

1)-Reverberation and Fullness of tone, 2)-Direct sound, Early Sound, Reverberant Sound, 3)-Early Decay Time-EDT,. 4)-Speed of Successive Tones, 5) - Definition or Clarity, 6) - Resonancy, 7)-Intimacy or Presence and Initial Time –Delay Gap, 8)-Liveness or Mid Frequencies, 9) - Spaciousness, 10)-Warmth, 11)-Listener Envelopment, 12) - Strength of sound and Loudness,. 13)-Timbre and Tone

Colour, 14)-Acoustical glare, 15)-Brilliance, 16) - Balance. 17)-Blend,. 18)-Ensamble. 19)-Immediacy of response (Attack), 20)-Texture, 21) –Echoes,. 22)-Dynamic Range, and Background Level, 23)-Detriments to Tonal Quality., 24)- Uniformity of sound in Audience areas.

2.1 Chronological Order

In the following table, a list of acoustic parameters, in chronological order, we present:

Year	Parameter	Author	Reference
1922	Reverberation Time	Sabine	[1]
1930	Reverberation Time Eyring	Eyring, Norris	[5]
	Reverberation Time Milingtone	Milingtone	[6]
1933	Reverberation Time Milingtone	Sette	[7]
1953	D50-Definition	Thiele	[8]
1953	D80-Definition	Thiele	[8]
1959	Reverberation Time Fitzroy	Fitzroy	[9]
1961	Signal-to-noise ratio	Lochner y Burger	[10]
1962	Br, Brilliance	Beranek	[11]
1962	Timbre, BR	Beranek,	[11]
1962	Texture	Beranek	[11]
1965	R-reverberance	Beranek	[12]
1965	Hallmas	Beranek, Shultz	[12]
1965	Steepness	Schroeder	[13]
1966	Hallabstand	Reichardt, Schmidt	[14]
1967	ASW, apparent source width	Marshall	[15]
1968	BQI,Binaural Quality Index	Keet	[4]]
1970	EDT, Early Decay Time	Jordan	[16]
1971	Ts, Center Time	Kürer,R.	[17]

Year	Parameter	Author	Reference
			[18]
1971	LF,Lateral Fraction	Barron	[19]
1971	Alcons	Peutz	[41]
1973	K, Korrelationsgrad	Gottlob	[20]
1974	C50, Clarity 50, speech	Reichard y Abdel Alim	[21]
1974	C80-Clarity 80, music	Reichard y Abdel Alim	[21]
1974	IACC, Interaural Cross Correlation	Schroeder/ Ando	[22]
1975	Inversion Index	Jordan	[23]
1976	Reverberation Time, Kuttruff	Kuttruff	[24]
1976	G-Strenght	Lehmann	[25]
1976	S-Spectral Density	Eyshold	[26]
1979	ITDG	Davis	[27]
1980	STI, Speech Transmission Index	Steenek, Houtgast	[28]
1980	C7-direct sound level	Ahnert	[29]
1980	LE, lateral efficiency	Jordan	[30]
1981	SI-Spatial impression	Barron	[18]
1982	Rise Time	Jordan	[31]
1983	ITDG2	Ando	[32]
1985	RASTI, Rapid Speech Transmission Index	Steenek, Houtgast	[33]
1986	EK speech	Dietsch	[34]
1986	EK music	Dietsch	[34]
1988	RECC, Reflective Energy Cumulative Curve	Toyota	[35]
1989	LFC, lateral fraction coefficient	Kleiner	[36]
1989	EEL,Early Ensemble Level	Gade	[37] [38]
1995	LEV,Listener Envelopment	Bradley, Soloudre	[39]
1999	Reverberation Time Neubauer	Neubauer	[40]
2004	[1-IACCE3], BQI	Beranek	[4]

2.2 Acoustic Quality Criteria Order

At present, the parameters descriptors of the concert acoustics halls can be grouped in the following three generic criteria:

a) – Energy Criteria, studying the transparency of the hall (separated perception of tones in the time and the instruments playing simultaneously), among which the most important are: Definition introduced by Thiele in 1953 [8], Clarity defined by Abdel Alim and Reichardt in 1974 [21], G-Strenght defined in 1976 by Lehmann [25].

b) - Time Criteria that quantify the Reverberation. (degree of the hall liveliness). The most known is the Reverberation Time [1] developed later by Eyring -1930, Millington - 1933, Fitzroy-1959, Kuttruf-1976, in Spain by Higiní Arau. - 1988 [42], Neubauer-1999.

Furthermore, it was established the equations for calculation of T10, T20, T30. For the time being EDT (Early Decay Time) defined by Jordan in 1970, is considered the most representative parameter by the majority of the investigators.

c) - Spatial Criteria, to define the space Impression (feeling like surrounded by the sound, get the impression of small room and near the sound source).

Parameters like: Lateral Fraction (LF), defined by Marshall and developed by Barron or the similar parameter Lateral Efficiency (LE), defined by Jordan. In 1968 Keet [4] proposes the BQI, that later will define the form [1-IACC3]. A very important binaural parameter that was introduced by Schroeder and Ando, in 1974, is Interaural Cross Correlation (IACC) with its two components the IACCE and the IACCL.

Due to the importance of the space impression, the acousticians continue developing this line with other quantification parameters like: apparent source width (ASW) defined by Marshall and developed by Barron that becomes a subjective parameter of the space in the concert halls and is related to the level of the early lateral reflections. Marshal and Barron developed the equations for the ASW calculation.

Another component of the spatiality is LEV (listener envelopment), and describes generally the impression of a listener being surrounded by the sound. Beranek [4] considers that the IACCL can be considered a parameter of measurement for LEV. According to Bradley and Soloudre [39] the level of the delayed lateral energy can measure the LEV. The IACCE measures the apparent source width ASW and IACCL measures the envelopment of listener LEV.

Year	Time Criteria	Autor
1922	Reverberation Time	Sabine
1930	Reverberation Time Eyring	Eyring, Norris
	Reverberation Time	Millington
1933	Millington	Sette
	Reverberation Time	Fitzroy
1959	Fitzroy	Fitzroy
1962	Timbre, Bass Ratio	Beranek
1962	Br, brilliance	Beranek

Year	Time Criteria	Author
1962	Texture	Beranek
1965	Steepness	Schroeder
1970	Early Decay Time	Jordan
1975	Inversion Index	Jordan
1976	Reverberation Time Kuttruff	Kuttruff
1979	Initial Time Delay GAP	Davis
1982	Rise Time	Jordan
1983	ITDG2	Ando
1988	Reflective Energy Cumulative Curve	Toyota
1999	Reverberation Time Neubauer	Neubauer
Year	Energy Criteria	Author
1953	Definition	Thiele
1965	Hallmass	Beraneck, Shultz
1966	Hallabstand	Reichardt, Schmidt Reichardt, Lehmann, Abdel Alim
1974	Clarity	Lehmann
1976	Strength	Lehmann
1971	Centre Time	Cremer-Kurer
1976	S, Spectral Density	Eysholdt
1982	EEB, Early Energy Balance	Jordan
Year	Spatial criteria	Author
1960	SDI, Surface Diffusivity Index	Haan, Fricke
1960	SI, spatial Impression	Barron, Marshall
1960	RR, index of roomresponse	Dresden school
1971	LF, Lateral Fraction	Barron, Marshall
1973	K, Correlation degree	Gottlob
1974	IACC, Interaural Cross Corelation	Ando
1974	IACCE, Interaural Cross Corelation, early	
1974	IACCL, Interaural Cross Correlation, late	
1980	LE, Lateral Efficiency	Jordan
1989	LFC, Lateral Fraction Coefficient	Kleiner
Year	Stage criteria	Author
1989	EEL-Early Essembly Level	Gade
1989	Room suport, ST1(2)	Gade

Year	Speech Criteria	Author
1953	D50, Definition	Thiele
1971	ALcons	Peuz
1980	C-50, Clarity	Ahnert
1985	RASTI-STI	Steeneken, Houtgast
1986	Echo criterio	Dietsch

2.3 Alfabetical Order Index

[1-IACC3], Beranek, 2004
ASW, Apparent Source Width, Marshall, 1967
BQI, Binaural Quality Index, Keet, 1968
Br, Brilliance, Beranek, 1962
BR, Bass ratio, Beranek, 1962
C7, Direct sound measure, Ahnert, 1980
C80, Clarity, Abdel Alim y Reichardt, 1974
D80, Definition, Thiele-1953
EDT, Early Decay Time, Jordan, 1980
EEB, Early Energy balance-Jordan, 1982
EEL, Early Ensemble Level, Gade, 1989
EK music (Echo criterion), Dietsch, 1986
G, Strenght, Lehmann, 1976
Hallabstand, Reichardt y Schmidt, 1966
Hallmass, Beranek y Schultz, 1965
IACC, Interaural Cross Corelation, Ando, Schroeder, 1974
IACCE, Interaural Cross Corelation Early, Schroeder, 1974
IACCL, Interaural Cross Correlation Late, Schroeder, 1974
II, Inversion Index, Jordan, 1975
ITDG, Initial Time Delay Gap, Davis, 1979
ITDG2, Ando, 1983
K, Korrelationsgrad, Gottlob, 1973
LE, Lateral Eficiency, Jordan, 1980
LEV, Listener envelopement, Bradley, 1995
LFC, Lateral Fraction Coefficient, Kleiner, 1989
LF, Lateral Fraction, Lateral, Marshall, Barron, 1983.
RASTI, Rapid Speech Transmission Index, Steenek,
Houtgast, 1985
RECC, Reflective Energy Cumulative Curve, Toyota, 1988
Ratio Signal-to-noise, Lochner y Bruger-1961
R-Reverberance Measure-Beranek, 1965
Reverberation Time, Arau, 1988
Reverberation Time, Eyring, 1930
Reverberation Time, Fitzroy, 1959
Reverberation Time, Kuttruff, 1976
Reverberation Time, Milingtone, 1933
Reverberation Time, Neubauer, 1999
Reverberation Time, Sabine, 1922

TR, Rise time, Jordan, 1982
 Ts, Center Time, Cremer-Kürer, 1971
 S-Spectral Density -Eysholdt 1976
 SI, Spatial Impression, Barron, Marshall, 1981
 S, Steepness, Schroeder, 1965
 ST1/2-Soporte-Support-Gade, 1989
 STI-Speech Transmission Index, Steenek, Houtgast, 1980

3 Conclusions

The paper presents a review concerning the historical evolution of the acoustic concert halls parameters, at the international level. Since the bibliography about these is fragmented, we performed in this article a global and updated presentation on the chronology and the evolution of the studied parameters and, where is possible, indicates articles or publications where they have been presented for the first time, to serve to the researcher interested in the room acoustics study.

4 Bibliography References

[1]-Sabine, W. Collected Papers on Acoustics (1922). (Harvard University Press.Reimpresión Dover, 1964).*

[2]-Giménez A.P., Sanchis,A.M, Sanchis, A.S., Romero J.F, Cerdá S.J, Vanacloy., J.Ma. -Estudio de la evolución de parámetros acústicos que miden la calidad de salas de conciertos, *TecniAcustica* 2001, La Rioja, España

[3]-Proyecto de investigación “Establecimiento de parámetros acústicos determinantes de la calidad percibida en salas de concierto y auditorios. Propuesta para su aplicación e proyectos de nueva planta o rehabilitación” BIA2003-09306-C04, Plan Nacional de I+D

[4]-Beranek, L.L.- Concert halls and Opera Houses-Music, Acoustic and Architecture, Springer-Verlag New York, 2004, ISBN 0-387-95524-0, p.506

[5]-Eyring, C.F. “Reverberation Time in “Dead” Rooms”, *The Journal of the Acoustical Society of America*, Vol. 1, 217-241 (1930)

[6]-Millington, G. “A Modified Formula for Reverberation”, *The Journal of the Acoustical Society of America*. Vol. 4, (1932), pp 69-82

[7]-Sette,W.H. “A New Reverberation Time Formula”, *The Journal of the Acoustical Society of America*. Vol. 4, (1933), pp 193-210

[8]- R. Thiele, Richtungsverteilung und Zeitfolge der Schallruckwürfe in Raumen. *ACUSTICA* 3 (1953), p. 291.

[9]-Fitzroy, D.-“Reverberation formulae which seems to be more accurate with non-uniform distribution of absorption”, *The Journal of the Acoustical Society of America*, Vol. 31, 893-897 (1959)

[10]-Lochner, J. P. A., Burger,J. F.“The intelligibility of speech under reverberant conditions”, *Acustica* 11, 195–200 (1961).

[11]-Beranek, L. L.- Music, Acoustics and Architecture, John Wiley and Sons New York, London 1962

[12]-Beranek, L.L., Schultz, T. J Some recent experiences in the design and testing.: of concert halls with suspended panel arrays *Acustica* 15 (1965), 307

[13]-Schroeder, M.R.: New method of measuring reverberation time *JASA* 38 (1965), S. 329 and 40, S. 549

[14]-Reichardt, W; Schmidt, W-Die Hörbaren Stufen des Raumeindrucks bei Musik, *Acustica* 17, 1966

[15]-Marshall,A.H “A note on the importance of room crosssection in concert halls,” *J. Sound Vib.*, 5, 100–112 (1967).

[16]-Jordan, V.L., 1970. "Acoustical Criteria for Auditoriums and Their Relation to Model Techniques".- *JASA*, Vol. 47, No. 2 (Part 1), pp. 408-412

[17]-Kürer, R.: Einfaches Messverfahren zur Bestimmung der „Schwerpunktzeit“ raumakustischer Impulsantworten (A simple measuring procedure for determining the "center time" of room acoustical impulse responses) 7th Intern. Congress on Acoustics, Budapest 1971

[18]-Barron, M., Spatial Impression due to Early Lateral Reflections in Concert Halls: The Derivation of a Physical Measure. *J. Sound and Vibration* 77(2) [1981] pp 211, 232

[19]- Barron,M., Auditorium Acoustics and Architectural Design Verlag E & FN SPON London 1993

[20]-Gottlob, “Vergleich Objektiver Akustischer Parameter mit Ergebnissen Subjektiver Untersuchungen aus Konzersälen” Thesis, Gottingen. 1973

[21]-Abdel Alim, O.:Abhängigkeit der Zeit- und Registerdurchsichtigkeit von raumakustischen Parametern bei Musikdarbietungen (Dependence of time and register definition of room acoustical parameters with music performances) Dissertation, TU Dresden 1973

[22]-Schroeder, M.R., Gottlob D., Siebrasse K.F.-Comparative study of European concert halls: correlation of subjective preference with geometric and acoustic parameters-*J. Acoust, Soc Am.*,V ol.5 6, No.4 , October 1974

[23]-Jordan, V. L. Comprehensive musical criterion: the Inversion Index., *J Audio Eng Soc* Mar, 1975 p 131-135

[24]-Kuttruff, H. “Nachhall und effektive Absorption in Räumen mit diffuser Wandreflexion”, *Acustica*, Vol. 35, No 3, 141-153 (1976)

[25]-Lehmann, P.: Über die Ermittlung raumakustischer Kriterien und deren Zusammenhang mit subjektiven Beurteilungen der Hörsamkeit (On the ascertainment of room acoustical criteria and correlation of the same with subjective assessments of the acoustic overall impression) Dissertation TU Berlin, 1976

[26]-Eysholdt, “Subjektive Untersuchungen and Digitalen Nachbildungen von Schallfeldern aus Konzersälen”, Thesis. Gottingen. 1976

[27]-Davis, D. "The role of Initial Time-Delay Gap in the Acoustic Design of Control Rooms for Recording and Reinforcing Systems". Sixty-fourth Audio. Engr. Soc. Convention, November 1979.

[28]-Steeneken, H.J.M.-Apsyhical Method for measuring Speech Transmission Quality-*J. Acoust. Soc. Am*, Vol 19 (1980)

- [29]-Ahnert, W.; Schmidt, W.-Acustik in Kulturbauten (Acoustics in cultural buildings), Institut für Kulturbauten, Berlin 1980
- [30]- Jordan, V. L.: Acoustical design of concert halls and theaters Applied Science Publishers Ltd. 1980
- [31]-Jordan, V.L., Acoustical criteria for concert hall stages, Applied Acoustics, Volume 15, Issue 5, September 1982, Pages 321-328
- [32]- Ando Y.-Calculation of subjective preference at each seat in a concert hall a), J. Acoust Soc.Am.,V ol.7 4, No.3 . September 1983, 873-887.*
- [33]- Review of the MTF concept in room acoustics and its use for use estimating speech intelligibility in auditoria- J. Acoust. Soc. Amer.77 (1985), p.1060-1077
- [34]- Dietsch, L.Kraak, W, Ein objektives Kriterium zur Erfassung von : Echostörungen bei Musik- und Sprachdarbietungen (An objective criterion for capturing echo disturbances with music and speech performances) Acustica 60 (1986), p 205
- [35]Toyota, Y, et al., JASA, Vol. 84 (S1), 1988.
- [36]-Kleiner, M.: A New Way of Measuring Lateral Energy Fractions App. Acoust., Vol. 27, 321 ff (1989
- [37]- Gade, A.C.: Investigations of musicians' room-acoustic conditions in concert halls. Part I: Methods and laboratory experiments Acustica 69 (1989), p 193
- [38]- Gade, A.C.: Investigations of musicians' room-acoustic conditions in concert halls. Part II: Field experiments and synthesis of results Acustica 69 (1989), S. 249
- [39]Bradley JS, Soulodre GA. Objective measures of listener envelopment. Journal of the Acoustical Society of America 1995; 98; 2590–7]
- [40]-Neubauer, R.O. “Prediction of Reverberation Time in Rectangular Rooms with a Modified Fitzroy Equation”, ISSEM'99, 8th International Symposium on Sound Engineering and Mastering, Gdansk, Poland, 115 - 122 (1999)
- [41]-Peutz, V.M.A- Articulation Loss of Consonants as a criterion for Speech Transmission in a Room-J. Audio Eng. Soc. Vol 19(1971), p. 915-919
- [42]-Arau-Puchades, H., An Improved Reverberation Formula. Acústica, Vol. 65, 1988.